



FLEXICS® S07BQ-F

PUR cable for submersible motor pumps,
unscreened

SPECIAL CABLES

Extremely robust cable for extreme environmental conditions. The PUR outer sheath meets the highest requirements for tear and abrasion resistance. Excellent weather resistance, very good chemical resistance and microbial safe. Halogen-free and resistant to UV rays.



TECHNICAL DATA



Test Voltage
3000 V / 50 Hz



Rated Voltage
450/750 V (U₀/U)



Bending radius (min.)
Fixed installation: 5 x ϕ of cable
Flexible use: 7,5 x ϕ of cable



Core identification
Colours according to CENELEC HD 308 S2 or black (continuously numbered) with green/yellow ground conductor



Temperature range
Operating temperature: -40°C up to 90°C
Conductor temperature: max. 90°C
Short circuit temperature: max. 200°C

DESIGN



- 1 Bare copper conductors, fine wires class 5 according to DIN EN 60228 / VDE 0295 / IEC 60228
- 2 Core insulation of special compound based on cross-linked polymer (XLPE)
- 3 Cores are stranded together with optimal lay-length
- 4 Special polyurethane (PUR) outer sheath, colour: yellow (RAL 1021)

Number of cores x nominal cross-section (mm ²)	Outer diameter appr. (mm)	Cu-value (kg/km)	Total weight appr. (kg/km)
4 G 1.5	10.1	57.6	126
5 G 1.5	11.1	72	152
7 G 1.5	13.3	100.8	212
10 G 1.5	15.7	144	291
4 G 2.5	11.5	96	180
7 G 2.5	16.8	168	340
4 G 4	14.1	153.6	270
4 G 6	16.6	230.4	385
4 G 10	21.5	384	662
4 G 16	25.1	614.4	958

CONTACT PERSON

Dipl. Ing. Peter Tomka
+421 37 6969631
peter.tomka@ics-cables.sk

