



H07Z-R

Insulated wire, halogen-free, multi core

HALOGEN-FREE INSTALLATION CABLES

For fixed installation in conduits on or under plaster. Suitable for protected installation in and on lighting facilities or control devices for voltages up to 750 V AC or 1,000 V DC against ground. Suitable for hotels, hospitals, underground railways, airports etc. to protect people and technical building equipment in the event of fire.



TECHNICAL DATA



Standard
EN 50525-3-41



Test Voltage
2.5 kV



Rated Voltage
450/750 V (U₀/U)



Bending radius (min.)
4 x Ø of wire



Fire properties
EN 60332-1-2: flame retardant
EN 60754-1 and 2: halogen-free; non-corrosive
combustion gases
EN 61034-2: low smoke emission
CPR classification: Eca



Core identification
HD 308 S2

DESIGN



1

Copper conductor, stranded wire (-R)

2

Core insulation (XLPE)

Nominal cross-section (mm ²)	Core colours	Max. conductor resistance (Ω/km)	Outer diameter appr. (mm)	Total weight appr. (kg/km)	Standard lengths/packing (m)
6	bk, bn, bu, gnye	3.1	5	65	500 T, 1000 T
10	bk, bn, bu, gnye	1.8	6.5	110	500 T, 1000 T
16	bk, bn, bu, gnye	1.2	7.5	175	500 T, 1000 T
25	bk, bn, bu, gnye	0.7	9	275	500 T, 1000 T
35	bk, gnye	0.5	10	365	500 T, 1000 T
50	bk, gnye	0.4	12	490	500 T, 1000 T
70	bk, gnye	0.3	14	700	500 T, 1000 T
95	bk, gnye	0.2	1	920	500 T, 1000 T
120	bk, gnye	0.2	18.5	1150	500 T, 1000 T
150	bk, gnye	0.1	20.5	1400	500 T, 1000 T
185	bk, gnye	0.1	22.5	1760	500 T, 1000 T
240	bk, gnye	0.1	25.5	2300	500 T, 1000 T

CONTACT PERSON

Dogan Özcan
 Head of Technical Department
 +43 (0) 1 70170-154
 dogan.oezcan@skw.at

