



We Make
Modern Life
Possible



NA2XS2Y 12/20 kV

XLPE/PE medium voltage aluminium underground cable

For fixed installation for high requirements in the ground subject to external effects of moisture, in the open air and in cable ducts for industrial and distribution mains – as permitted by the local building regulations – under severe mechanical stressing during installation and operation.



TECHNICAL DATA



Standard
DIN VDE 0276-620



Certificate
VDE Germany



Test Voltage
36 kV / 50 Hz



Rated Voltage
12/20 kV (U₀/U)



Bending radius (min.)
15 x Ø of cable



Temperature range
Laying temperature: min. -20°C
Operating temperature: -50°C up to 90°C
Conductor temperature: max. 90°C
Short circuit temperature: max. 250°C

DESIGN



Number of cores x nominal cross-section / cross-section of screen (mm ²)	Mutual capacitance max (nF/km)	Max. conductor resistance (Ω/km)	Current rating in the earth (A)	Current rating in the air (A)	Outer diameter appr. (mm)	Total weight appr. (kg/km)	Standard lengths/packing (m)
1 x 35 RM / 16	0.16	0.868	146	155	25	600	500 T, 1000 T
1 x 50 RM / 16	0.18	0.641	172	185	29.1	780	500 T, 1000 T
1 x 70 RM / 16	0.2	0.443	210	231	30.6	880	500 T, 1000 T
1 x 50 RM / 25	0.14	0.641	174	187	34.1	990	500 T, 1000 T
1 x 70 RM / 25	0.15	0.443	213	232	35.4	1090	500 T, 1000 T
1 x 150 RM / 25	0.26	0.206	319	366	35.1	1280	500 T, 1000 T
1 x 185 RM / 25	0.27	0.164	361	420	36.7	1430	500 T, 1000 T
1 x 240 RM / 25	0.31	0.125	417	496	38.8	1630	500 T, 1000 T
1 x 400 RM / 35	0.37	0.0778	535	660	43.8	2250	500 T, 1000 T

CONTACT PERSON**Dogan Özcan**

Head of Technical Department
+43 (0) 1 70170-154
dogan.oezcan@skw.at

