



We Make
Modern Life
Possible



SiA

Silicone insulated wire

SILICONE CABLES

This wire is well suited for internal wiring in lamps, instruments, control panels and distributors for low mechanical stress particularly at high ambient temperatures.



TECHNICAL DATA



Standard
adapted to DIN VDE 0250



Test Voltage
2 kV



Rated Voltage
300/500 V (U₀/U)



Bending radius (min.)
4 x Ø of cable




Fire properties
EN 60332-1-2: flame retardant



Temperature range
Laying temperature: min. -50°C
Operating temperature: -50°C up to 180°C
Conductor temperature: max. 180°C
Short circuit temperature: max. 350°C

DESIGN



Nominal cross-section (mm ²)	Core colours	Max. conductor resistance (Ω/km)	Outer diameter appr. (mm)	Total weight appr. (kg/km)	Standard lengths/packing (m)
0.5	sw, ws	36.7	1.8	8	100 R
0.75	sw, ws	24.8	2	10	100 R
1	sw, ws	18.2	2.2	13	100 R
1.5	sw, ws	12.2	2.6	20	100 R
2.5	sw, ws	7.56	3.2	32	100 R
4	sw, ws	4.7	3.7	48	100 R
6	sw, rtbr	3.11	4.2	68	100 R
10	rtbr	1.84	5.9	116	100 R

CONTACT PERSON

Dogan Özcan
 Head of Technical Department
 +43 (0) 1 70170-154
dogan.oezcan@skw.at

