



NFA2X

XLPE insulated bundled overhead line

INSULATED OVERHEADLINES

Conductors are designed for outdoor distribution of electrical energy in suspended design.



TECHNICAL DATA



Standard

DIN VDE 0276-626 (HD 626)

ČSN 34 7614-4F

ČSN 34 7614-9F



Certificate

VDE Germany



Test Voltage

4 kV / 50 Hz



Rated Voltage

0.6/1 kV



Bending radius (min.)

18 x Ø of cable



Core identification

1, 2 resp. 3 raised longitudinal ribs on the surface of the cores. The surface of the neutral conductor is smooth.



Temperature range

Laying temperature: min. -20°C

Operating temperature: -30°C up to 80°C

Conductor temperature: max. 80°C

Short circuit temperature: max. 130°C

DESIGN



1

Aluminium conductor with increased breaking load, round stranded compressed (RM)

2

Core insulation (XLPE black, UV-resistant); 2 or 4 cores of equal cross section are stranded together in left-hand lay, additionally 1 or 2 cores of reduced cross section can be co-stranded

Number of cores x nominal cross-section [mm ²]	Max. conductor resistance (Ω/km)	Min. breaking load of conductor strand (kN)	Current rating in the air (A)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
1 x 16 RM*	1.91	2.5	72	8	75
2 x 16 RM*	1.9	2.5	81	15.6	150
4 x 16 RM*	1.91	2.5	81	18.8	290
1 x 25 RM	1.2	4	107	9	110
2 x 25 RM*	1.2	4	107	18	210
4 x 25 RM	1.2	4	107	21.2	430
1 x 35 RM	0.868	5.5	132	10	135
2 x 35 RM*	0.868	5.5	132	20	270
4 x 35 RM	0.868	5.5	132	24.1	555
1 x 50 RM	0.641	8	165	11.8	185
2 x 50 RM*	0.641	8	165	23.5	365
4 x 50 RM	0.641	8	165	27.8	750
4 x 50 x 25 RM/RM*	0.641 / 1.2	8	165	31.9	815
4 x 50 x 35 RM/RM*	0.641 / 0.868	8	165	31.9	845
1 x 70 RM	0.443	10.7	205	13.4	255
4 x 70 RM	0.443	10.7	205	31.8	1010
4 x 70 x 25 RM/RM*	0.443 / 1.2	10.7	205	36	1110
4 x 70 x 35 RM/RM	0.443 / 0.868	10.7	205	36.2	1150
4 x 70 + 2 x 35 RM/RM	0.443 / 0.868	10.7	205	40.1	1290
1 x 95 RM*	0.32	13.7	240	15.4	335
4 x 95 RM*	0.32	13.7	250	37.8	1340
4 x 95 x 25 RM/RM*	0.32 / 1.2	13.7	250	41.8	1440
4 x 95 x 35 RM/RM*	0.32 / 0.868	13.7	250	41.8	1470
4 x 95 + 2 x 25 RM/RM*	0.32 / 1.2	13.7	250	42	1550
1 x 120 RM*	0.253	18.6	290	17	410
4 x 120 RM*	0.253	18.6	290	40.5	1600
1 x 150 RM*	0.206	23.2	334	19	505

CONTACT PERSON

Ing. Dan Bachtik
Product Supervisor
+420734366090
dan.bachtik@prakab.cz

