




(N)HXCH FE180/E30-E60 (VDE)

SiR/FRNC halogen-free energy cable with insulation integrity and circuit integrity, screened

SAFETY CABLES WITH CIRCUIT INTEGRITY


These cables are intended for the stationary distribution of electrical energy in dry or damp premises and for fixed installations in air or concrete. Suitable for hotels, hospitals, underground railways, airports etc. to protect people and technical building equipment in the event of fire.. Not allowed for installations underground or in water. These cables are not UV-protected.



TECHNICAL DATA

Standard adapted to DIN VDE 0266	Bending radius (min.) 12 x Ø of cable (multicore) 15 x Ø of cable (singlecore)	Core identification HD 308 S2
Certificate VDE Germany	Fire properties EN 60332-1-2: flame retardant EN 60754-2: halogen-free, non-corrosive combustion gases EN IEC 60332-3-24: reduced flame propagation EN 61034-2: low smoke emission IEC 60331-21, DIN VDE 0472-814: insulation integrity FE 180 DIN 4102-12: circuit integrity	Temperature range Laying temperature: min. -5°C Operating temperature: -50°C up to 90°C Conductor temperature: max. 90°C Short circuit temperature: max. 250°C
Test Voltage core/core 4 kV / 50 Hz		
Rated Voltage 0.6/1 kV		

DESIGN



- 1 Copper conductor, round solid (RE) resp. round stranded (RM)
- 2 Core insulation (silicone rubber)
- 3 Inner covering (halogen-free tape and halogen free polymer compound)
- 4 Concentric screen (bare copper wires), counter helix (copper tape) and halogen-free plastic tape
- 5 Sheath (halogen-free polymer compound, orange)

Number of cores x nominal cross-section / cross-section of screen (mm ²)	Max. conductor resistance (Ω/km)	Current rating in the air (A)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
2 x 1.5 RE / 1.5	12.1	28	14	249
3 x 1.5 RE / 1.5	12.1	25	14.5	274
4 x 1.5 RE / 1.5	12.1	25	15.4	309
5 x 1.5 RE / 1.5	12.1	16	16.4	348
7 x 1.5 RE / 2.5	12.1	15.5	17.4	420
10 x 1.5 RE / 2.5	12.1	13	20.9	572
12 x 1.5 RE / 2.5	12.1	12.5	21.4	618
14 x 1.5 RE / 2.5	12.1	12	22.3	676
19 x 1.5 RE / 4	12.1	10.5	24.3	831
24 x 1.5 RE / 6	12.1	9.5	28.5	1091
30 x 1.5 RE / 6	12.1	9	30	1245
40 x 1.5 RE / 10	12.1	8	33.9	1590
2 x 2.5 RE / 2.5	7.41	37	14.8	296
3 x 2.5 RE / 2.5	7.41	33	15.4	330
4 x 2.5 RE / 2.5	7.41	33	16.3	376
5 x 2.5 RE / 2.5	7.41	22	17.4	427
7 x 2.5 RE / 2.5	7.41	20.5	18.6	513
10 x 2.5 RE / 4	7.14	17.5	23	732
12 x 2.5 RE / 4	7.14	16.5	23.6	798
14 x 2.5 RE / 6	7.14	15	24.6	898
19 x 2.5 RE / 6	7.14	14	26.9	1103
24 x 2.5 RE / 10	7.14	12.5	31.5	1443
30 x 2.5 RE / 10	7.14	12	33.2	1657
40 x 2.5 RE / 10	7.14	11	37	2084
2 x 4 RE / 4	4.61	49	16.2	362
3 x 4 RE / 4	4.61	43	16.9	409
4 x 4 RE / 4	4.61	43	18	471
5 x 4 RE / 4	4.61	28	19.2	537
7 x 4 RE / 4	4.61	27	20.5	651
10 x 4 RE / 6	4.61	27	24.7	930
12 x 4 RE / 6	4.61	27	25.4	1022
14 x 4 RE / 6	4.61	27	26.5	1129
19 x 4 RE / 10	4.61	25	29.6	1452
2 x 6 RE / 6	3.08	62	17.2	445
3 x 6 RE / 6	3.08	54	18	510
4 x 6 RE / 6	3.08	54	19.1	591
5 x 6 RE / 6	3.08	36	20.5	678
2 x 10 RE / 10	1.83	85	19.2	600
3 x 10 RE / 10	1.83	75	20.1	701
4 x 10 RE / 10	1.83	75	21.4	824
5 x 10 RE / 10	1.83	49	23.1	962
2 x 16 RM / 16	1.15	113	21.5	834
3 x 16 RM / 16	1.15	100	22.5	992
4 x 16 RM / 16	1.15	100	24.2	1175
5 x 16 RM / 16	1.15	65	26.1	1380
1 x 25 RM / 16	0.727	152	15.2	535
3 x 25 RM / 16	0.727	136	26.5	1388
4 x 25 RM / 16	0.727	136	28.6	1670
5 x 25 RM / 16	0.727	90	31.2	1997
1 x 35 RM / 16	0.524	217	16.4	640
3 x 35 RM / 16	0.524	165	28.9	1733
4 x 35 RM / 16	0.524	165	31.3	2117



Number of cores x nominal cross-section / cross-section of screen (mm ²)	Max. conductor resistance (Ω/km)	Current rating in the air (A)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
5 x 35 RM / 16	0.524	165	34.3	2558
1 x 50 RM / 16	0.387	265	18.2	786
3 x 50 RM / 25	0.387	201	32.8	2326
4 x 50 RM / 25	0.387	201	35.9	2855
5 x 50 RM / 25	0.387	201	39.4	3441
3 x 70 RM / 35	0.268	255	38.1	3171
4 x 70 RM / 35	0.268	255	41.6	3902
5 x 70 RM / 35	0.268	255	45.6	4707
3 x 95 RM / 50	0.193	314	43	4261
4 x 95 RM / 50	0.193	314	47.1	5266
5 x 95 RM / 50	0.193	314	51.8	6366
3 x 120 RM / 70	0.153	364	46.1	5277
4 x 120 RM / 70	0.153	364	50.6	6526
5 x 120 RM / 70	0.153	364	55.9	7901
1 x 150 RM / 16	0.124	557	25.7	1828
3 x 150 RM / 70	0.124	416	50.7	6338
4 x 150 RM / 70	0.124	416	55.8	7880
5 x 150 RM / 70	0.124	416	61.5	9534
3 x 185 RM / 95	0.099	480	56.5	8001
4 x 185 RM / 95	0.099	480	62.1	9896
4 x 240 RM / 120	0.075	565	69.5	12673

CONTACT PERSON

Dogan Özcan
 Head of Technical Department
 +43 (0) 1 70170-154
 dogan.oezcan@skw.at

