



We Make
Modern Life
Possible



FLEXICS® CHAIN SERVO 911

PP/PUR servo-motor supply cable, halogen-free for
drag chain application, unscreened

AUTOMATION AND MOTOR SUPPLY CABLES

Highly flexible PP/PUR connection cable for frequency converters and servo motors, especially for continuous moving machine parts, e.g. within C-tracks. FLEXICS® CHAIN SERVO 911 cables are designed for indoor applications when exposed to high mechanical stress and increased resistance against a wide range of oils, greases, coolants and lubricants.



TECHNICAL DATA



Test Voltage
4000 V / 50 Hz



Rated Voltage
0.6/1 kV (U₀/U)



Bending cycles
5 million



Bending radius (min.)
Fixed installation: 5 x $\varnothing$ of cable
Flexible use: 7.5 x $\varnothing$ of cable



Fire properties
EN 60332-1-2: self-extinguishing and flame retardant



Core identification
Supply cores: black (continuously numbered) with green/yellow ground conductor
control cores: black with number printing



Temperature range
Fixed installation: -50°C up to 80°C
Flexible use: -30°C up to 80°C

DESIGN



- 1 Bare copper conductors, super fine wires class 6 according to DIN EN 60228 / VDE 0295 / IEC 60228
- 2 Core insulation of special compound based on polypropylene (PP)
- 3 Control pairs individually screened with plastic laminated aluminium tape and tinned copper wires
- 4 Cores stranded together in short lay-lengths
- 5 Non-woven tape separation
- 6 Special polyurethane (PUR) outer sheath, colour: orange (RAL 2003) or grey (RAL 7001)

Number of cores x nominal cross-section (mm ²)	Outer diameter appr. (mm)	Cu-value (kg/km)	Total weight appr. (kg/km)
4 G 1.5 + 2 x (2 x 0.75)	14.0	96	235
4 G 1.5 + (2 x 1)	12.0	87	186
4 G 2.5 + 2 x (2 x 0.75)	14.6	134	291
4 G 2.5 + (2 x 1)	12.7	125	241
4 G 4 + (2 x 0.75) + (2 x 1)	16.1	206	370
4 G 4 + (2 x 1)	14.8	182	326
4 G 6 + (2 x 0.75) + (2 x 1)	17.6	283	472
4 G 6 + (2 x 1)	16.4	259	433

CONTACT PERSON

Dipl. Ing. Peter Tomka
+421 37 6969631
peter.tomka@ics-cables.sk

