



We Make
Modern Life
Possible



E-A2Y

PE insulated bundled overhead line

INSULATED OVERHEADLINES

Can be used for fixed installation as overhead power lines up to 1,000 V inclusive. Not suitable for direct burial.



TECHNICAL DATA



Standard
ÖVE/ÖNORM E 8200-626 (HD 626)



Test Voltage
3,5 kV / 50 Hz



Rated Voltage
0,6/1 kV



Bending radius (min.)
18 x Ø of cable



Core identification
1, 2 resp. 3 raised longitudinal ribs on the surface of the cores, the 4. core is showing fine longitudinal grooves (75 % of surface) and is printed with the type designation



Temperature range
Laying temperature: min. -5°C
Operating temperature: -50°C up to 70°C
Conductor temperature: max. 70°C
Short circuit temperature: max. 160°C

DESIGN



1

Aluminium conductor, round stranded (RM)

2

Core insulation (PE black, UV-resistant)

Number of cores x nominal cross-section (mm ²)	Max. conductor resistance (Ω/km)	Current rating in the air (A)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
2 x 16 RM	1.91	56	14.2	131
2 x 25 RM	1.2	80	17.9	210
4 x 25 RM	1.2	80	21.5	410
4 x 35 RM	0.868	100	24.1	522
4 x 50 RM	0.641	125	28.1	702
4 x 70 RM	0.443	160	31.9	958
4 x 95 RM	0.32	185	37.2	1308

CONTACT PERSON

Dogan Özcan
 Head of Technical Department
 +43 (0) 1 70170-154
 dogan.oezcan@skw.at

