



H05BQ-F (NGMH11YÖ)

PUR Insulated wire

PUR CABLES

For use in dry, damp or wet rooms with medium mechanical stress. The cables are primarily used in industrial enterprises and construction sites under demanding operating conditions, especially with demanding operating conditions, especially abrasive and grinding stresses.



TECHNICAL DATA



Standard
EN 50525-2-21



Test Voltage
2 kV



Rated Voltage
300/500 V (U₀/U)



Bending radius (min.)
3 x Ø der Leitung (feste Verlegung)
5 x Ø der Leitung (freie Verlegung)



Core identification
HD 308 S2



Temperature range
Laying temperature: min. -40°C
Conductor temperature: max. 90°C
Short circuit temperature: max. 200°C
Fixed installation: -40°C up to 75°C
Flexible use: -25°C up to 75°C

DESIGN



Number of cores x nominal cross-section (mm ²)	Max. conductor resistance (Ω/km)	Outer diameter appr. (mm)	Total weight appr. (kg/km)	Standard lengths/packing (m)
2 x 0,75	26,7	6,6	46	500 Sp, 1000 Sp
3 G 0,75	26,7	7,2	59	500 Sp, 1000 Sp
3 x 0,75	26,7	7,2	59	500 Sp, 1000 Sp
4 G 0,75	26,7	7,8	81	500 Sp, 1000 Sp
5 G 0,75	26,7	8,8	90	500 Sp, 1000 Sp
2 x 1	20,0	7,1	53	500 Sp, 1000 Sp
3 G 1	20,0	7,5	67	500 Sp, 1000 Sp
4 G 1	20,0	8,2	84	500 Sp, 1000 Sp
5 G 1	20,0	10,2	107	500 Sp, 1000 Sp

CONTACT PERSON

Dogan Özcan
Head of Technical Department
+43 (0) 1 70170-154
dogan.oezcan@skw.at

