



CYKYLo

Flat PVC/PVC installation cables

INSTALATION AND HARMONISED CABLES AND WIRES

The cables are designed for fixed power distribution under the plaster, in sanitary units, in pipes and rails.



TECHNICAL DATA

 <p>Standard ČSN 34 7411</p>	 <p>Rated Voltage 450/750 V</p>	 <p>Core identification ČSN 33 0166 ed. 2</p>
 <p>Certificate EZÚ Czech Republic</p>	 <p>Bending radius (min.) 6 cable height: Bending of the cable is only possible in its shorter axis</p>	 <p>Temperature range Laying temperature: min. -5°C Operating temperature: -40°C up to 70°C</p>
 <p>Test Voltage 2.5 kV / 50 Hz</p>	 <p>Fire properties EN 60332-1-2: self-extinguishing OPR classification: Eca</p>	<p>Conductor temperature: max. 70°C Short circuit temperature: max. 160°C</p>

DESIGN



- 1 Copper conductor, round solid (RE)
- 2 Core insulation (PVC)
- 3 Sheath (PVC black, UV-resistant)

Number of cores x nominal cross-section (mm ²)	Max. conductor resistance (Ω/km)	Current rating in the earth (A)	Width of flattened conductor (mm)	Height of flattened conductor (mm)	Total weight appr. (kg/km)
2 x 1.5 RE	12.531	22	6.7	3.9	60
3 x 1.5 RE	12.531	19	9.5	3.9	80
2 x 2.5 RE	7.52	30	7.5	4.3	85
3 x 2.5 RE	7.52	25	10.7	4.3	120

CONTACT PERSON

Ing. Štěpán Laštůvka
Product Supervisor
+420 732 912 682
stepan.lastuvka@prakab.com

