



We Make
Modern Life
Possible



FLEXICS® SERVO C UL/c(UL)

UL recognized PVC/PVC servo-motor supply cable,
screened

AUTOMATION AND MOTOR SUPPLY CABLES

PVC/PVC connection cable especially for frequency converters and servo motors. FLEXICS® SERVO C UL/c(UL) cable are designed for fixed or flexible indoor installations without guidance and/or tensile stress, especially when excellent EMC behaviour is required.



TECHNICAL DATA



Certificate

UL AWM Style 20886
CSA C22.2 No. 210-11, AWM



Test Voltage

4000 V / 50 Hz



Rated Voltage

0.6/1 kV (U₀/U)
1000 V (UL/CSA)



Bending radius (min.)

Fixed installation: 7,5 x Ø of cable



Fire properties

EN 60332-1-2: self-extinguishing and flame retardant
UL: vertical flame test VW-1, cable flame test
CSA: FT1



Core identification

Supply cores: black (continuously numbered) with green/yellow ground conductor
Control pairs 0.34 mm²: colour coded
Control pairs from 0.75 mm²: black with white numbers



Temperature range

Fixed installation: -30°C up to 80°C

DESIGN



- 1 Bare copper conductors, fine wires class 5 according to DIN EN 60228 / VDE 0295 / IEC 60228
- 2 Core insulation of special compound based on polyvinyl chloride (PVC)
- 3 Control pairs individually screened with plastic laminated aluminium tape and tinned copper wires
- 4 Cores are stranded in layers with optimal lay-length
- 5 Plastic tape separation
- 6 Tinned copper wire braiding
- 7 Non-woven tape separation over braiding (optional)
- 8 Outer sheath of special compound based on polyvinyl chloride (PVC), colour: grey (RAL 7001)

Number of cores x nominal cross-section (mm ²)	Outer diameter appr. (mm)	Cu-value (kg/km)	Total weight appr. (kg/km)
4 G 0.75 + 2 x (2 x 0.34)	12.4	111	225
4 G 1.5 + 2 x (2 x 0.75)	14.8	148	343
4 G 2.5 + (2 x 2 x 0.75)	16.1	226	407
4 G 4 + (2 x 0.75 + 2 x 1)	17.6	304	498
4 G 6 + (2 x 0.75 + 2 x 1)	19.2	379	627
4 G 10 + (2 x 0.75 + 2 x 1)	23.0	592	909
4 G 16 + (2 x 2 x 1)	25.1	861	1190
4 G 25 + (2 x 2 x 1.5)	28.7	1262	1854
4 G 35 + (2 x 2 x 1.5)	30.6	1652	2023
4 G 50 + (2 x 2 x 2.5)	37.0	2264	2876

CONTACT PERSON

Dipl. Ing. Peter Tomka
 +421 37 6969631
 peter.tomka@ics-cables.sk

