



E-AYY-J or -O

PVC/PVC aluminium energy cables

ALUMINIUM 0.6/1 kV

Power distribution cable for power stations, industrial facilities and switching stations as well as for local power networks. For fixed installation indoors, in cable ducts, outdoors and in water, according to the applicable erection standards, if no risk of any mechanical damage is to be expected.



TECHNICAL DATA

<p>Standard ÖVE/ONORM E 8200-603 (HD 603)</p>	<p>Rated Voltage 0.6/1 kV</p>	<p>Core identification HD 308 S2</p>
<p>Certificate EZÚ Czech Republic ÖVE Austria</p>	<p>Bending radius (min.) 12 x Ø of cable (multicore) 15 x Ø of cable (singlecore);</p>	<p>Temperature range Laying temperature: min. -5°C Operating temperature: -50°C up to 70°C Conductor temperature: max. 70°C Short circuit temperature: max. 140°C</p>
<p>Test Voltage core/core 4 kV / 50 Hz</p>	<p>Fire properties EN 60332-1-2: self-extinguishing OPR: Eca</p>	

DESIGN



- 1 Aluminium conductor, round solid (RE), sector-shaped solid (SE), round stranded (RM), resp. sector-shaped stranded (SM)
- 2 Core insulation (PVC)
- 3 Inner covering (EPDM or plastic tape)
- 4 Sheath (PVC black, UV-resistant)

Number of cores x nominal cross-section (mm ²)	Max. conductor resistance (Ω/km)	Current rating in the earth (A)	Current rating in the air (A)	Outer diameter appr. (mm)	Total weight appr. (kg/km)	Standard lengths/packing (m)
1 x 25 RM	1.2	160	110	12.1	197	500 D, 1000 D
1 x 35 RM	0.868	193	135	13.1	237	500 D, 1000 D
1 x 50 RM	0.868	230	166	14.8	301	500 D, 1000 D
1 x 70 RM	0.443	283	210	16.3	380	500 D, 1000 D
1 x 95 RM	0.32	340	259	18.5	494	500 D, 1000 D
1 x 120 RM	0.253	389	302	19.8	581	500 D, 1000 D
1 x 150 RM	0.206	436	345	21.7	697	500 D, 1000 D
1 x 185 RM	0.164	496	401	24.2	870	500 D, 1000 D
1 x 240 RM	0.125	578	479	27.0	1092	500 D, 1000 D
1 x 300 RM	0.1	654	550	29.7	1324	500 D
1 x 400 RM	0.078	756	653	33.4	1652	500 D
1 x 500 RM	0.061	873	772	36.9	2071	500 D
1 x 630 RM	0.047	1011	915	42.4	2593	500 D
3 x 25 RM	1.2	102	81	22.5	712	500 D, 1000 D
3 x 35 RM	0.868	122	99	25.0	895	500 D, 1000 D
3 x 50 SM	0.641	144	119	25.3	809	500 D, 1000 D
3 x 70 SM	0.443	179	152	28.1	1041	500 D, 1000 D
3 x 95 SM	0.32	215	186	31.5	1365	500 D, 1000 D
3 x 120 SM	0.253	245	216	34.0	1628	500 D, 1000 D
3 x 150 SM	0.206	275	246	38.0	2012	500 D, 1000 D
3 x 150 + 70 SM/SM	0.206	275	246	40.5	2300	500 D, 1000 D
3 x 185 SM	0.164	313	285	41.6	2462	500 D, 1000 D
3 x 185 + 95 SM/RM	0.164	313	285	49.6	2977	500 D, 1000 D
3 x 240 SM	0.125	364	338	47.2	3207	500 D
3 x 240 + 120 SM/RM	0.125	364	338	55.1	3728	500 D
4 x 25 RM	1.2	102	81	25.0	860	500 D, 1000 D
4 x 35 SM	0.868	122	99	24.3	798	500 D, 1000 D
4 x 50 SE	0.641	144	119	26.4	983	500 D, 1000 D
4 x 50 RM	0.641	144	119	28.1	1039	500 D, 1000 D
4 x 50 SM	0.641	144	119	28.1	1039	500 D, 1000 D
4 x 70 SM	0.443	179	152	30.9	1334	500 D, 1000 D
4 x 95 SM	0.32	215	186	36.4	1809	500 D, 1000 D
4 x 120 SM	0.253	245	216	39.3	2160	500 D, 1000 D
4 x 150 SE	0.206	275	246	40.4	2463	500 D, 1000 D
4 x 150 SM	0.206	275	246	43.9	2620	500 D, 1000 D
4 x 185 SM	0.164	313	285	49.6	3314	500 D, 1000 D
4 x 240 SM	0.125	364	338	55.1	4191	500 D
4 x 300 SM	0.1	419	400	61.9	5238	500 D
5 x 16 RM	1.91	92	72	22.6	720	500 D
5 x 25 RM	1.2	102	81	27.4	1019	500 D, 1000 D
5 x 50 SM	0.641	144	119	29.4	1256	500 D, 1000 D
5 x 70 SM	0.443	179	152	34.8	1676	500 D, 1000 D
5 x 95 SM	0.32	215	186	38.6	2216	500 D, 1000 D
5 x 120 SM	0.253	245	216	43.3	2658	500 D, 1000 D
5 x 150 SM	0.206	275	246	48.3	3313	500 D, 1000 D
5 x 185 SM	0.164	313	285	54.1	4095	500 D, 1000 D
5 x 120 RM	0.253	245	216	47.0	3201	500 D
5 x 150 RM	0.206	275	246	56.0	4300	500 D
5 x 240 SM	0.125	364	338	64.7	5369	500 D



CONTACT PERSON

Dogan Özcan
Head of Technical Department
+43 (0) 1 70170-154
dogan.oezcan@skw.at

