



TCEKPFLEY

PE/PVC railway safety ground cables, screened

RAILWAY SIGNALLING AND TELECOMMUNICATIONS CABLES

The cables are waterproof and designed for cable ducting, laying in the ground, and for external environment for railway telecommunication, control and signaling systems.



TECHNICAL DATA

 <p>Standard TP PRAKAB 02/00</p>	 <p>Rated Voltage 380 V</p>	 <p>Core identification TP PRAKAB 02/00</p>
 <p>Certificate EZÚ Czech Republic</p>	 <p>Bending radius (min.) 10 x Ø of cable</p>	 <p>Temperature range Laying temperature: min. -10°C Operating temperature: -40°C up to 70°C</p>
 <p>Test Voltage core/core 3 kV / 50 Hz core/screen 3 kV / 50 Hz</p>	 <p>Fire properties EN 60332-1-2: self-extinguishing CPR: Eca</p>	

DESIGN



- 1 Copper conductor, round solid (RE)
- 2 Core insulation (foam skin PE), cores star quaded and quads stranded in groups, core stranding petrol jelly filled
- 3 Inner covering (paper tape)
- 4 Concentric screen (PE-Al-PE tape)
- 5 Sheath (PE, black)
- 6 Sheath (PVC black, UV-resistant)

Electrical parameters

Conductor diameter	mm	1
Loop resistance max	Ω/km	50
Conductor resistance, max. at 20 °C	Ω/km	10
Capacitance unbalance, max. k	pF/m	0.83
Mutual capacitance, max.	nF/km	60
Impedance at 800 Hz	Ω	390
Attenuation at 800 Hz	dB/km	0.7

Number of pairs x nominal diameter	Outer diameter appr. (mm)	Total weight appr. (kg/km)
2 x 2 x 1	17.4	297
3 x 2 x 1	16.9	294
4 x 2 x 1	17.8	332
6 x 2 x 1	19.8	414
7 x 2 x 1	19.8	426
12 x 2 x 1	23.1	589
16 x 2 x 1	25.2	712
24 x 2 x 1	28.6	937
30 x 2 x 1	30.9	1098
48 x 2 x 1	36.5	1568
61 x 2 x 1	40.0	1888

CONTACT PERSON

Ing. Štěpán Laštůvka
Product Supervisor
+420 732 912 682
stepan.lastuvka@prakab.com

