



We Make
Modern Life
Possible



FLEXICS® SPIRAL 11

PVC/PUR multicore control cable, coilable

SPECIAL CABLES

Our FLEXICS® SPIRAL 11 cables have been developed for indoor applications exposed to light or medium mechanical stress. They possess an increased resistance against a wide range of oils, greases, coolants and lubricants. They have a very good elasticity and offer more memory than its PVC alternative. Used mainly in households, lighting, mechanical and plant engineering. Further spiral processing possible.



TECHNICAL DATA



Test Voltage
4000 V / 50 Hz



Rated Voltage
300/500 V (U₀/U)



Core identification
Colour coded or continuously numbered according to internal standards or customer requirements



Temperature range
Operating temperature: -5°C up to 70°C

DESIGN



- 1 Bare copper conductors, fine wires class 5 according to DIN EN 60228 / VDE 0295 / IEC 60228
- 2 Core insulation of special compound based on polyvinyl chloride (PVC)
- 3 Cores are stranded in layers with optimal lay-length
- 4 Mineral powder separation
- 5 Special polyurethane (PUR) outer sheath, shiny finished, colour: grey (RAL 7001), other colours upon request

Number of cores x nominal cross-section (mm ²)	Outer diameter appr. (mm)	Cu-value (kg/km)	Total weight appr. (kg/km)
2 x 0.75	5.7	14.4	42
3 G 0.75	6.1	21.6	52
4 G 0.75	6.7	28.8	65
5 G 0.75	7.3	36.0	78
7 G 0.75	8.0	50.0	98
12 G 0.75	10.1	86.4	166
18 G 0.75	12.2	129.6	237
2 x 1	6.1	19.2	49
3 G 1	6.6	28.8	64
4 G 1	7.1	38.4	78
5 G 1	7.6	48.0	94
7 G 1	8.5	67.0	117
12 G 1	11.0	115.2	204
18 G 1	13.1	172.8	286
2 x 1.5	6.5	29.0	62
3 G 1.5	7.1	43.0	79
4 G 1.5	7.5	57.6	105
5 G 1.5	8.6	72.0	123
7 G 1.5	9.6	101.0	163
12 G 1.5	12.7	172.8	279
18 G 1.5	14.9	259.2	398
3 G 2.5	8.6	72.0	123
4 G 2.5	9.2	96.0	158
5 G 2.5	10.5	120.0	189

CONTACT PERSON

Dipl. Ing. Peter Tomka
+421 37 6969631
peter.tomka@ics-cables.sk

