



PRAFlaSafe XD

1-CXKHDH-R B2ca s1a d1 a1 XLPE/FRNC copper energy cable, halogen-free, armoured, UV-resistant

LOW VOLTAGE CABLES 0,6/1 kV

Cables are designed for fixed distribution of electricity in ordinary environment in hotels, hospitals, subway, airports, etc., to protect people and technical equipment of buildings in case of fire, where there is no requirement to maintain the functionality of the entire cable installation in fire. In case of fire, the cable releases a small amount of heat and smoke. The cables are UV-resistant.



TECHNICAL DATA

<p> Standard ČSN 34 7660-100 TP PRAKAB 02/99</p> <hr/> <p> Certificate EZÚ Czech Republic</p> <hr/> <p> Test Voltage core/core 4 kV / 50 Hz</p> <hr/> <p> Rated Voltage 0,6/1 kV</p>	<p> Bending radius (min.) 6 x Ø up to 20 mm 12 x Ø from 20 mm to 40 mm 15 x Ø over 40 mm</p> <hr/> <p> Fire properties ČSN EN 60332-1-2: self-extinguishing ČSN EN 60754-2: halogen-free, non-corrosive combustion gases ČSN EN 61034-2: low smoke emission ČSN EN 60332-3-22: reduced flame propagation ČSN EN 13501-6: fire classification CPR: B2ca s1a d1 a1</p>	<p> Core identification ČSN 33 0166 ed. 2, ČSN EN 50334</p> <hr/> <p> Temperature range Laying temperature: min. -5°C Operating temperature: -50°C up to 60°C Conductor temperature: max. 90°C Short circuit temperature: max. 90°C</p>
--	--	---

DESIGN



- 1 Copper conductor, round solid (RE) resp. round stranded (RM)
- 2 Core insulation (XLPE)
- 3 Inner covering (halogen-free tape and halogen free polymer compound)
- 4 Inner sheath (halogen-free polymer compound)
- 5 Armouring (galvanized steel wires)
- 6 Sheath (halogen-free polymer compound, orange, UV resistant)

Number of cores x nominal cross-section (mm ²)	Max. conductor resistance (Ω/km)	Current rating in the air (A)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
2 x 1.5 RE	12.1	28	15.1	490
3 x 1.5 RE	12.1	24	15.5	521
4 x 1.5 RE	12.1	24	16.2	560
5 x 1.5 RE	12.1	16	16.9	614
7 x 1.5 RE	12.1	16	17.7	685
12 x 1.5 RE	12.1	13	22.0	1001
19 x 1.5 RE	12.1	11	24.6	1241
24 x 1.5 RE	12.1	10	27.3	1481
2 x 2.5 RE	7.41	37	15.8	551
3 x 2.5 RE	7.41	32	16.3	591
3 x 2.5 RE	7.41	32	16.3	591
4 x 2.5 RE	7.41	22	17.1	640
5 x 2.5 RE	7.41	22	18.2	713
7 x 2.5 RE	7.41	21	19.3	825
12 x 2.5 RE	7.41	18	23.8	1210
19 x 2.5 RE	7.41	14	26.5	1524
24 x 2.5 RE	7.41	13	30.0	1865
2 x 4 RE	4.61	49	16.7	610
3 x 4 RE	4.61	42	17.2	673
4 x 4 RE	4.61	42	18.3	757
5 x 4 RE	4.61	28	19.5	844
7 x 4 RE	4.61	27	21.3	1027
12 x 4 RE	4.61	22	25.8	1467
19 x 4 RE	4.61	-	28.9	1879
2 x 6 RE	3.08	62	17.7	708
3 x 6 RE	3.08	53	18.5	784
4 x 6 RE	3.08	53	19.7	899
5 x 6 RE	3.08	36	21.6	1063
2 x 10 RE	1.83	85	20.9	967
2 x 10 RM	1.83	85	21.3	998
3 x 10 RE	1.83	74	21.7	1085
3 x 10 RM	1.83	74	22.1	1118
4 x 10 RE	1.83	74	22.9	1237
4 x 10 RM	1.83	74	23.6	1283
5 x 10 RE	1.83	49	24.7	1434
5 x 10 RM	1.83	49	25.3	1476
2 x 16 RE	1.15	113	22.7	1182
2 x 16 RM	1.15	113	23.5	1243
3 x 16 RE	1.15	98	23.8	1372
3 x 16 RM	1.15	98	24.6	1422
4 x 16 RE	1.15	98	25.5	1591
4 x 16 RM	1.15	98	26.2	1646
5 x 16 RE	1.15	65	27.2	1828
5 x 16 RM	1.15	65	28.0	1888
3 x 25 RM	0.727	133	28.5	1929
4 x 25 RM	0.727	133	30.6	2259
5 x 25 RM	0.727	90	32.8	2615
4 x 35 RM	0.524	162	33.0	2774
5 x 35 RM	0.524	109	35.9	2448
4 x 50 RM	0.387	197	39.7	4301
5 x 50 RM	0.387	133	42.6	4993





CONTACT PERSON

Ing. Štěpán Laštůvka
Product Supervisor
+420 732 912 682
stepan.lastuvka@prakab.com

