



# V-VMvKsas

PVC/PVC/PVC aluminium energy cables, screened

LOW VOLTAGE CABLES 0,6/1 kV



## TECHNICAL DATA



**Standard**  
NEN HD 603-3I



**Test Voltage**  
core/core 4 kV / 50 Hz



**Rated Voltage**  
0,6/1 kV



**Bending radius (min.)**  
installation/pulling: 12 x  $\phi$  of cable  
fixed/final installation: 10 x  $\phi$  of cable  
transport: 15 x  $\phi$  of cable



**Fire properties**  
EN 60332-1-2: self-extinguishing  
CPR classification: Eca



**Core identification**  
VDEN: red, yellow, blue, yellow/blue



**Temperature range**  
Operating temperature: -15°C up to 70°C  
Conductor temperature: max. 70°C  
Short circuit temperature: max. 200°C

## DESIGN



- 1 Aluminium conductor, sector-shaped solid (Alsvm)
- 2 Core insulation (PVC)
- 3 Cores stranded together in lay-lengths
- 4 Inner covering (EPDM and PVC, black)
- 5 Inner covering (EPDM)
- 6 Concentric screen (bare copper wires applied with changing direction of lay) and counter helix (copper tape)
- 7 Sheath (PVC grey RAL 7001)

Number of cores x nominal cross-section / cross-section of screen (mm <sup>2</sup> )	Average insulation thickness of main cores (mm)	DC resistance main core R <sub>dc</sub> at 20 °C	Current rating in the earth acc. NEN 1010	Current rating in the air (A)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
4 x 95 Alsvm / 35	1.6	0.32	255	189	44.9	3230
4 x 150 Alsvm / 50	1.8	0.206	325	246	52.0	4590
4 x 240 Alsvm / 70	2.2	0.125	427	339	63.4	6840

**CONTACT PERSON**

**Ing. Štěpán Laštůvka**  
Product Supervisor  
+420 732 912 682  
stepan.lastuvka@prakab.com

