




(N)AYY

PVC/PVC aluminium energy cables

LOW VOLTAGE CABLES 0,6/1 kV

The cables are designed for distribution of electrical energy in fixed installation in the ground, cable ducts and in the external environment.



TECHNICAL DATA



Standard
adapted to DIN VDE 0276-603 (HD 603)



Rated Voltage
0,6/1 kV



Core identification
HD 308 S2



Certificate
VDE Germany



Bending radius (min.)
12 x Ø of cable



Temperature range
Laying temperature: min. -5°C
Operating temperature: -50°C up to 70°C
Conductor temperature: max. 70°C
Short circuit temperature: max. 140°C




Test Voltage
core/core 4 kV / 50 Hz



Fire properties
EN 60332-1-2: self-extinguishing
CPR: Eca

DESIGN



Aluminium conductor, sector-shaped stranded (SM)



Core insulation (PVC)



Inner covering (EPDM)



Sheath (PVC black, UV-resistant)

Number of cores x nominal cross-section (mm ²)	Max. conductor resistance (Ω/km)	Current rating in the air (A)	Current rating in the earth (A)	Outer diameter appr. (mm)	Total weight appr. (kg/km)
5 x 50 SM	0.641	82	99	33.5	1767
5 x 70 SM	0.443	107	126	38.6	2268
5 x 95 SM	0.32	131	151	43.1	2972
5 x 120 SM	0.253	151	171	48.2	3542
5 x 150 SM	0.206	173	193	52.9	4259
5 x 185 SM	0.164	197	216	59.1	5225
5 x 240 SM	0.125	235	253	69.6	6703

CONTACT PERSON

Jan Pietroň
Key Account Manager
+420 604 471 907
jan.pietron@koneka.cz

